



GLOCK 43X



FRONT SIGHT
polymer



SLIDE STOP LEVER
standard

TRIGGER CONFIGURATION
triggerspring01 / connector 7 /
firing pin spring 24N (silver)



REAR SIGHT
polymer



MAGAZINE
10 rds



MAGAZINE CATCH
reversible



www.glock.com

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.



TECHNICAL DATA



CALIBER

9x19



MAG. CAPACITY

10 rds



BARREL PROFILE

hexagonal (GMB)



BARREL LENGTH

mm in.

87 3,41



LENGTH OF TWIST

mm in.

250 9,84



WEIGHT

without magazine

g oz

465 16,40



WEIGHT

with empty magazine

g oz

530 18,70



WEIGHT*

with loaded magazine

g oz

654 23,07



TRIGGER TRAVEL

mm in.

12,5 0,49

TRIGGER PULL

N lbf

24 5,4

* depending on the ammunition used

DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	165	6,50
2. SLIDE LENGTH (cpl.)	154	6,06
3. WIDTH (OVERALL)	28	1,10
4. SLIDE WIDTH	22	0,87
5. HEIGHT INCL. MAGAZINE	128	5,04
6. SIGHT RADIUS (POLYMER)	133	5,24
SIGHT RADIUS (STEEL)	132	5,20
SIGHT RADIUS (GNS)	131	5,16
7. TRIGGER DISTANCE	67	2,64
8. BARREL DISTANCE	19	0,75